

Standard grease gun-HHFP

G 1/8"-GBDR-MU

Item number: 12 632 482

Discount group: A



Technical data

| | |
|--|--|
| Grease gun connection, pressure-side: | G 1/8" |
| Capacity (cm ³): | 500 |
| Refilling options: | 400 g grease cartridge, DIN 1284, or bulk grease using a spatula |
| Diameter of grease piston (mm): | 8 |
| Grease pump piston actuation: | manually lever operated |
| Delivery rate/stroke (cm ³): | 1,2 at a grease density of 0.92 kg/dm ³ , tested with grease cartridge 400 g (12 511) |
| Discharge pressure up to (bar): | 400 |
| Burst pressure system (bar): | 850 |
| Burst pressure grease gun head (bar): | 1200 |
| Operation of plunger rod: | with L-design handle |
| Sealing cover: | loose |
| Wall thickness of grease gun tube (mm): | 1,0 |
| Lacquering: | silver |
| Dimensions LxWxH (mm): | 395 x 120 x 66 |
| Weight (kg): | 1,25 |

Specification

- Spout, angled, G 1/8", 150 mm (12 735)
- Coupler, 4 jaws, G 1/8" (12 731)

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- plunger with exactly fitting when using bulk grease or cartridge
- acc. to DIN 1283
- TÜV - certified
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- sure grip handling due to deep band knurls
- safe handle on the plunger rod
- Slip resistant handle on grease gun lever
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

Packaging

| | |
|--------------------------------|-------------------------------------|
| Package: | Polybag, printed, with EAN bar code |
| Dimensions LxWxH (mm): | 400 x 360 x 145 |
| Weight including package (kg): | 13,2 |
| Packing unit: | 10.0 |