



### One hand grease gun-EHFP

125 cm<sup>3</sup>-G 1/8"-GRDR-MU

**Item number:** 12 276  
**EAN:** 4103810122767  
**Discount group:** A

#### Technical data

Grease gun connection, pressure-side: G 1/8"  
Filling nipple: M 10 x 1  
Capacity (cm<sup>3</sup>): 125  
Refilling options: grease gun filling system or bulk grease  
Diameter of grease piston (mm): 8  
Grease pump piston actuation: manual, by means of pressure grip  
Delivery rate/stroke (cm<sup>3</sup>): 0,4  
Discharge pressure up to (bar): 550  
Burst pressure system (bar): 850  
Burst pressure grease gun head (bar): 1200  
Operation of plunger rod: with L-design handle  
Sealing cover: loose  
Wall thickness of grease gun tube (mm): 1,0  
Lacquering: silver  
Dimensions LxWxH (mm): 275 x 145 x 55  
Weight (kg): 0,53

#### Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- Spout, straight, G 1/8" a, 150 mm (12 475)
- Coupler, 4 jaws, G 1/8" (12 731)
- Sales package, with Bar code

#### Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Contoured plunger, tight fitting, with bulk grease
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Grease gun head, zinc die casting Z 410
- safe handle on the plunger rod
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease
- High-speed ventilation, by half a rotation of the grease gun tube

#### Packaging

Dimensions LxWxH (mm): 285 x 120 x 55  
Weight including package (kg): 0,65  
Packing unit: 1.0